

AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions and listings of claims in the application.

LISTING OF CLAIMS

1. (Currently Amended) A pattern forming method of forming linear film patterns by arranging droplets of a liquid material discharged from a plurality of discharge portions on a substrate, comprising:

defining a plurality of pattern forming areas arranged with a pitch which is larger than that of the discharge portions, in which the film patterns are to be formed, on the substrate, the areas including:

a first pattern forming area in which a film pattern is to be formed from a side thereof; and

a second pattern forming area in which a film pattern is to be formed from the center thereof; and

arranging the droplets ~~whose width is smaller than that of the film pattern in the side of the first pattern forming area~~ at the side thereof and arranging the droplets in the center of the second pattern forming area at the center thereof to form the film patterns, the droplets arranged in each of the side of the first pattern forming area and the center of the second pattern forming area contacting each other, and the droplets arranged in the first pattern forming area and the droplets arranged in the second pattern forming area being entirely formed of a same material; and

wherein the discharge portions are provided corresponding to the first and second pattern forming areas, and the droplets are arranged while moving the discharge portions in the direction in which the pattern forming area are arranged.

2. (Original) The pattern forming method according to Claim 1, wherein the method comprises a step of substantially simultaneously arranging the droplets in the first and second pattern forming areas.

3. (Original) The pattern forming method according to Claim 1, wherein the method comprises a step of arranging the droplets in only one of the first and second pattern forming areas.

4. (Original) The pattern forming method according to Claim 1, wherein in the first pattern forming area, the side is first formed and then the central portion is formed, and in the second pattern forming area, the central portion is first formed and then the side is formed.

5. (Original) The pattern forming method according to Claim 1, wherein a plurality of discharge portions for arranging the droplets are provided corresponding to the first and second pattern forming areas, and the droplets are arranged while moving the discharge portions in the direction in which the pattern forming areas are arranged.

6. (Original) The pattern forming method according to Claim 1, the method further comprising:

a step of forming one side of a first film pattern to be formed in the first pattern forming area;

a step of forming a central portion of a second film pattern to be formed in the second pattern forming area at the same time as forming the other side of the first film pattern; and

a step of forming one of one side and the other side of the second film pattern at the same time as forming a central portion of the first film pattern.

7. (Currently Amended) A pattern forming method of forming linear film patterns by arranging droplets of a liquid material discharged from a plurality of discharge portions on a substrate, the method comprising, when a plurality of the film patterns are arranged with a pitch which is larger than that of the discharge portions and formed on the substrate:

a first step of arranging the droplets ~~whose width is smaller than that of the film pattern~~ and forming a first area of a first film pattern of the plurality of film patterns;

a second step of arranging the droplets ~~whose width is smaller than that of the film pattern~~ and forming a first area of a second film pattern at the same time as forming a second area of the first film pattern; and

a third step of arranging the droplets ~~whose width is smaller than that of the film pattern~~ and forming a second area of the second film pattern at the same time as forming a third area of the first film pattern;

wherein the discharge portions are provided corresponding to the first and second film patterns,

the droplets are arranged while moving the discharge portions in the direction in which the film patterns are arranged, and

the droplets arranged in each of the first step, the second step, and the third step contact each other, and

the droplets are each formed entirely of the same material.

8. (Original) The pattern forming method according to Claim 7,
wherein the method further comprises a fourth step of forming a third area of the second film pattern after the third step.

9. (Original) The pattern forming method according to Claim 7,
wherein the liquid material comprises conductive particles.

10. – 16. (Cancelled)